

SEC. 9, T. 19 N., R. 9 E., W.M.





FILE NAME	O:\proj\Y2006\06-03475-002\CAD\D	vgs\51 EC3.dgn				· · · · · · · · · · · · · · · · · · ·
TIME	10:49:25 AM				REGION STATE	FED.AID PROJ.NO.
DATE	12/28/2007				NO.	
PLOTTED BY	tprescott			1	10 WAS	H
DESIGNED BY	G. KAYS	<u> </u>		1	JOB NUMBER	╡
ENTERED BY	T. PRESCOTT			1	141060G	
CHECKED BY	M. SPILLANE				CONTRACT NO.	· · · · · · · · · · · · · · · · · · ·
PROJ. ENGR.	D. EDWARDS			+	Y-9292	
REGIONAL ADM.	X. XXXXXXXXX	REVISION	DATE	BY	1-8282	







•	Washington State Department of Transportation
	HERRERA

	SR 410	
WHITE	RIVER - STABILIZE	SLOPES
	PROBLEM SITE 9	1

EROSION	CONTROL

51 o≠ 82 sheets






SECTION - SILT CURTAIN - NOT TO SCALE

GENERAL NOTES:

- 1. APPROVAL OF THE CONTRACTOR'S TEMPORARY WATER AND SEDIMENT CONTROL PLAN DOES NOT CONSTITUTE AN APPROVAL OF PERMANENT ROAD OR DRAINAGE DESIGN (E.G., SIZE AND LOCATION OF ROADS, PIPES, RESTRICTIONS, CHANNELS, RETENTION F
- THE IMPLEMENTATION OF EROSION AND SEDIMENT CONTROL (ESC) PLANS AND THE CONSTRUCTION, MAINTENANCE, REPLACEMENT, AND UPGRADING OF ESC FACILITIES IS THE RESPONSIBILITY OF THE CONTRACTOR UNTIL ALL CONSTRUCTION IS APPROVED
- 3. THE ESC FACILITIES SHOWN ON THE THIS PLAN MUST BE CONSTRUCTED PRIOR TO OR IN CONJUNCTION WITH ALL CLEARING AND GRADING SO. AS TO ENSURE THAT THE TRANSPORT OF SEDIMENT TO SURFACE WATERS, DRAINAGE SYSTEM, AND ADJACENT PROPERTIES IS MINIMIZED.
- 4. THE ESC FACILITIES SHOWN ON THIS PLAN ARE THE MINIMUM REQUIREMENTS FOR ANTICIPATED SITE CONDITIONS. DURING THE CONSTRUCTION PERIOD, THESE ESC FACILITIES SHALL BE UPGRADED AS NEEDED FOR UNEXPECTED STORM EVENTS AND MODIFIED TO ACCOUNT FOR CHANGING SITE CONDITIONS (E.G., ADDITIONAL SUMP PUMPS, RELOCATION OF DITCHES AND SITE FEBRURES FIX.)
- 5. THE ESC FACILITY SHALL BE INSPECTED DAILY BY THE CONTRACTOR'S ESC SUPERVISORS AND MAINTAINED TO ENSURE CONTINUED PROPER FUNCTIONING. WRITTEN RECORDS SHALL BE KEPT OF WEEKLY REVIEWS OF THE ESC FACILITIES.
- 6. ANY AREAS OF EXPOSED SOILS, INCLUDING ROADWAY EMBANKMENTS, THAT WILL NOT BE DISTURBED FOR SEVEN DAYS SHALL BE IMMEDIATELY STABILIZED WITH THE APPROVED ESC METHODS (E.G., SEEDING MULCHING, PLASTIC COVERING, ETC.).
- ANY AREA NEEDING ESC MEASURES THAT DO NOT REQUIRE IMMEDIATE ATTENTION SHALL BE ADDRESSED WITHIN SEVEN (7) DAYS.
- 8. THE ESC FACILITIES ON INACTIVE SITES SHALL BE INSPECTED AND MAINTAINED OR WITHIN TWENTY FOUR (24) HOURS FOLLOWING A STORM EVENT.
- STABILIZED CONSTRUCTION ENTRANCES AND ROADS SHALL BE INSTALLED AT THE BEGINNING OF CONSTRUCTION AND MAINTAINED FOR THE DURATION OF THE PROJECT, ADDITIONAL MEASURES, SUCH AS WASH PADS, MAY BE REQUIRED TO ENSURE THAT ALL PAVED AREAS ARE KEPT CLEAN FOR THE DURATION OF THE PROJECT.
- 19. WHERE STRAW MULCH FOR TEMPORARY EROSION CONTROL IS REQUIRED, IT SHALL BE APPLIED AT A MINIMUM THICKNESS OF 2 TO 3 INCHES.



DIVERSION NOTES:

PLACE 802 TYPE 1
GEOTEXTILE BELOW LINER

- 1 CF SANDBAG TO HOLD LINER

1. COBBLES AND BOULDERS REMOVED DURING DIVERSION CHANNEL SUB-GRADE PREPERATION SHALL BE STOCKPILED LOCALLY FOR REPLACEMENT DURING DIVERSION CHANNEL DECOMMISSIONING.


DETAIL - TYPICAL DIVERSION CHANNEL NOT TO SCALE

- 2. BULK BAGS SHALL HAVE POLY BAG LINERS.
- 3. MATERIAL USED TO FILL BULK BAGS SHALL BE APPROVED WASHED AGGREGATE OR NATIVE ALLUVIUM FROM ELJ CONSTRUCTION.
- 4. TYPE 1 GEOTEXTILE SHALL BE USED OVER PREPARED SUBGRADE TO PROVIDE CUSHION LAYER FOR GEOMEMBRANE LINER.
- 5. GEOMEMBRANE LINER SHALL BE REINFORCED 25 MILL POLYETHYLENE.
- 6. CONTRACTOR SHALL CONSTRUCT AND MAINTAIN A MINUMUM LINED CHANNEL DEPTH OF 6 FEET TALL.

SELECTIVELY REMOVE COBBLES AND BOULDERS LARGER THAN 1 FT. DIAMETER TO PREPARE DIVERSION CHANNEL SUBGRADE

- 7. UPSTREAM AND DOWNSTREAM ENDS OF DIVERSION CHANNEL GEOMEMBRANE LINER AND GEOTEXTILE LINER SHALL BE INSTALLED WITH ANCHOR TRENCHES.
- 8. GEOMEMBRANE SHALL BE SUPPLIED AND INSTALLED WITH MINIMAL WELDS.
- 9. ALL FIELD SEAMS SHALL OVERLAPPED A MINIMUM OF 8 FEET AND SHINGLED IN THE DOWNGRADIENT DIRECTION. TRANSVERSE SEAMS WILL NOT BE ALLOWED.

FILE NAME	O:\proJ\Y2006\06-03475-00	2\CAD\Dwgs\62 ECD1.dgn		-				T
TIME	11:42:29 AM			Г	REGION NO.	STATE	FED.AID PROJ.NO.	1
DATE	1/3/2008					15/4 611		ĺ
PLOTTED BY	tprescott				10	WASH		L
DESIGNED BY	G. KAYS				JOB M	UMBER		ľ
ENTERED BY	T. PRESCOTT				141	060G		ŀ
CHECKED BY	M. SPILLANE				CONTR	ACT NO.	LOCATION NO.	1
PROJ. ENGR.	D. EDWARDS				Y-9	292		ı
REGIONAL ADM.	X. XXXXXXXX	REVISION	DATE	BY				Į





CONSULTANTS

WHITE RIVER - STABILIZE SLOPES PROBLEM SITE 9

1 CF SANDBAG TO HOLD LINER


ECOLOGY BLOCK OR 1 CY BULK BAG (TYP.)

EROSION CONTROL DETAILS

ECD1 52


82 SHEETS


Plot 1



SEC. 9, T. 19 N., R. 9 E., W.M.

LEGEND:





FILE NAME	\$\$\$\$\$\$\$DESIGNFILENAME\$\$	\$\$\$\$				-		
TIME	\$TIME\$				REGION NO.	STATE	FED.AID PROJ.NO.	1
DATE	\$\$\$\$DATE\$\$\$					WASH		ı
PLOTTED BY	\$\$USERNAME\$\$				"	TTACI		١.
DESIGNED BY	R. KIRSCHBAUM				A BOL	NMBER		ŀ
ENTERED BY	T. PRESCOTT				141	060G		╛
CHECKED BY	M. SPILLANE				CONTE	ACT NO.	LOCATION NO.	ı
PROJ, ENGR.	D. EDWARDS				Y-9	292		١.
REGIONAL ADM.	X. XXXXXXXX	REVISION	DATE	BY				Ц







SR 410 WHITE RIVER - STABILIZE SLOPES PROBLEM SITE 9


DR1

DRAINAGE PLAN





SHEET TOTAL PROJECT TOTAL 3Y Robin Kirschbaum - Y - 3Y -				NO. STATE WASH 3 NUMBER 3760467	FED. AID PI	ROJ. NO.				Vashington Department	State of Transpo	ortation	W	SR 410 HITE RIVER - STABILIZE SLOPES
			REGION	IO. STATE	FED. AID PI	ROJ. NO.								
			1				I							1
	, 1											<u>-</u>		· ·
		+						-	<u> </u>					<u> </u>
		+				· - · · · · · · · · · · · · · · · · · ·								
														
-					-									·
oning to be determined													3	·
oning to be determined				_									1 1	
oning to be determined														ienticular bar
oning to be determined								-					4	4. Install new CB Type 1 and discharge to ELJ or
oning to be determined														Install new 5' wide by 4' tall box culvert
oning to be determined		+						-					1	
oning to be determined													2	Remove Existing Culvert
oning to be determined		+												energy dissipator
OCATION ∀ \ UNIT OF MEASURE ≻													. <u>-</u> .	Install new CB Type 1 and discharge to quarry sp
NAGET LATURE. OND NUMBER REFERS TO THE E FEATURE FOUND ON THAT SHEET.													SEE GENERAL N	
E SHEET REFERENCE NO. SHOWING											Ì		OTE	
													" l	
										Ì		ļ		
				· ·		· · ·			1	· 1	<u>.</u>	— Т		GENERAL NOTES:
					STRU	CTUR	E NOT	ES						
	AGE FEATURE. ND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. DCATION V \ UNIT OF MEASURE > ning to be determined ning to be determined	ON" BELOW REFERS TO THE SHEET E SHEET REFERENCE NO. SHOWING AGE FEATURE. ND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. POCATION V \ UNIT OF MEASURE > Ining to be determined	ON" BELOW REFERS TO THE SHEET E SHEET REFERENCE NO. SHOWING AGE FEATURE. ND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. POCATION V \ UNIT OF MEASURE > Ining to be determined	ON" BELOW REFERS TO THE SHEET E SHEET REFERENCE NO. SHOWING AGE FEATURE. ND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. POCATION > \ UNIT OF MEASURE > Ining to be determined	NUMBER OF THE "CODE ON" BELOW REFERS TO THE SHEET E SHEET REFERENCE NO. SHOWING AGE FEATURE. ND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. CATION ▼ \ UNIT OF MEASURE ➤ ning to be determined	NUMBER OF THE "CODE ON" BELOW REFERS TO THE SHEET E SHEET REFERENCE NO. SHOWING AGE FEATURE. ND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. DIATION ▼ \ \ UNIT OF MEASURE > Ining to be determined I	NUMBER OF THE "CODE ON" BELOW REFERS TO THE SHEET E SHEET REFERENCE NO. SHOWING AGE FEATURE. ND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. DCATION Y \ UNIT OF MEASURE > ning to be determined	NUMBER OF THE "CODE ON" BELOW REFERS TO THE SHEET E SHEET REFERENCE NO. SHOWING AGE FEATURE. ND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. DCATION ▼ \ UNIT OF MEASURE ➤ ning to be determined	ON' BELOW REFERS TO THE SHEET SHEET REFERENCE NO. SHOWING AGE FEATURE. ND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. DCATION Y \ UNIT OF MEASURE > ning to be determined	NUMBER OF THE "CODE ON" BELOW REFERS TO THE SHEET : SHEET REFERENCE NO. SHOWING AGE FEATURE. ND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. DCATION ▼ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	NUMBER OF THE "CODE ON" BELOW REFERS TO THE SHEET E SHEET REFERENCE NO. SHOWING AGE FEATURE. ID NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. CATION Y \ UNIT OF MEASURE > Ining to be determined Ining	NUMBER OF THE "CODE ON" BELOW REFERS TO THE SHEET E SHEET REFERENCE NO. SHOWING AGE FEATURE. ID NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. DCATION ▼ \ UNIT OF MEASURE ➤ Ining to be determined Ini	NUMBER OF THE 'CODE ON' BELOW REFERS TO THE SHEET SHEET REFERENCE NO. SHOWING AGE FEATURE. JD NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. DCATION ✓ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	NUMBER OF THE "CODE ON" BELOW REFERS TO THE SHEET SHEET REFERENCE NO. SHOWING AGE FEATURE. ### AND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. ### AND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. ### AND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. ### AND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. ### AND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. ### AND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. ### AND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. ### AND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. ### AND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. ### AND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. ### AND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. ### AND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. ### AND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. ### AND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. ### AND NUMBER REFERS TO THE FEATURE FOUND ON THAT SHEET. ### AND NUMBER REFERS TO THE ### AND NUMBER REFERS TO



IMPACT ABBREVIATIONS:

SBTI = STREAM BUFFER TEMPORARY IMPACT SBPI = STREAM BUFFER PERMANENT IMPACT STI = STREAM TEMPORARY IMPACT SPI = STREAM PERMANENT IMPACT WBPI = WETLAND BUFFER PERMANENT IMPACT

1. FINAL ALIGNMENT OF PARK PICNIC AREA ACCESS REALIGNMENT TO BE FINALIZED IN 60 PERCENT PLAN SET.

SEC. 9, T. 19 N., R. 9 E., W.M.

•	\	↑	SCALE IN FEET
	\	N	
	\	ייי	
	\		•
	\		
•	\		
	\		
		\	
•			
			•
		\	
		\	
		\	
		\	
		\	
		\	
		\ _E	
		HVF CG &	
PROPOSED DARK DIGNIG			
PROPOSED PARK PICNIC AREA ACCESS, SEE NOTE 1	HVF	HVF CG	
	- HVF CG	103	(]
HVF — HVF — CG-	- CG	HVF	WHI CHILLIAN IN THE CHILLIAN I
- HVF — HVF — CG — CG — SE		CHVF	
- CG CG 101 SF	CG UVF	Co HAL	
100	1 5 km		d
CG C		ON ON	w
- CG HVF	过星	OHA	\
<u>/</u>	4 [:]	OHW	\.
·	T. Far	DHM	\ '
SBPI = 0.100 Acres		U•	1
SBF1 - U.100 Acres	HVF		\
	M OHN	/	
ON ON	A.		A STATE OF THE STA
OHIV		<i>y</i> .	
OHN OHN OHN OHN	WHITE RIVE	<i>ج</i> ـ َ	ZANTY ZITY ZITY ZITY ZITY
OHM	ETAL	/	
NA.	MILE		۱۲۰
, o *	M.		, λ
			<i>*</i>
<i>•</i>	•		•
	/		
·			
<u> </u>			Plot 1

FILE NAME	O:\proj\Y2006\06-03475-002\CA	AD\Dwgs\ECP1.dgn					
TIME	2:53:14 PM				REGION NO.	STATE	FED.AID PROJ.NO.
DATE	12/5/2007					WASH	
PLOTTED BY	tprescott				10	WASH	
DESIGNED BY	G. KAYS				10B F		
ENTERED BY	T. PRESCOTT				141	060G	
CHECKED BY	M. SPILLANE				соит	VACT NO.	LOCATION NO.
PROJ. ENGR.	D. EDWARDS				Y-9	292	
REGIONAL ADM.	X. XXXXXXXXX	REVISION	DATE	BY			





SR 410 WHITE RIVER - STABILIZE SLOPES PROBLEM SITE 9

ECP1

5HEET 70

ENVIRONMENTAL COMPLIANCE PLAN

